

# Genwork Expanded Metal Mesh Raised Mesh

Expanded metal mesh has a diverse range of properties, which makes it extremely versatile for many uses and applications.

The mesh is formed from a single piece of metal, which means that there is nothing to work loose, no fretting strands or strained joints or welds.

## **Cutting Service**

In addition to stock panels we also offer a complete and comprehensive cut to size service, if you wish to have your panels cut to size or framed please follow the links below or down load planners.

'U' Edging Section Fabrication

Coatings - Self Colour, Galvanised, Bright Zinc plate and Powder Coated.

If you need anyhelp or advice please contact us.

Raised expanded metal is produced by slitting and drawing into an open mesh pattern in a single operation. The resulting expanded metal mesh is stronger and lighter than the original metal sheet.

Raised expanded metal is measured from the centre of the knuckle to the centre of the next, with the Long way measurment normally expressed first.

There are a large number of Raised meshes that are avalable, as listed below.

#### **Volume Discounts**

Quantities over +10 Panels = price on request

If there are any other forms of Raised mesh that you are looking for and not listed below, please don't hesitate to contact us

## **Our range**

Ref	Long Way	Short Way	Strand Width	Thickness	KG	Sheet Size LW x SW	Raw Material
06-20	5.84	3.50	0.79	0.60	2.11	1250x1250	Mild Steel
19-98	19.05	7.43	1.70	0.90	3.23	1250 x 2500	Mild Steel
28-96	28.58	9.52	1.98	1.20	3.92	2440 x 1220	Mild Steel
30-95	30.48	11.72	1.98	1.60	4.24	2440 x 1220	Mild Steel
38-97	38.10	16.48	2.25	1.60	3.43	2440 x 1220	Mild Steel
50-88	50.80	22.58	3.89	3.00	8.09	2440 x 1220	Mild Steel
50-89	50.80	22.58	3.12	3.00	6.52	2440 x 1220	Mild Steel
50-93	50.80	22.58	3.05	1.60	3.39	2440 x 1220	Mild Steel
76-92	76.20	33.87	3.58	3.00	4.97	2440 x 1220	Mild Steel
85-96	85.73	40.64	3.18	3.00	3.67	2440 x 1220	Mild Steel



# **Genwork Expanded Metal Mesh**Raised Mesh

10-95	101.60	50.80	5.03	3.00	4.66	2440 x 1220	Mild Steel
10-97	101.60	50.80	3.35	3.00	3.11	2440 x 1220	Mild Steel
11-99	114.30	39.33	4.60	3.00	5.48	2440 x 1220	Mild Steel
06-01A	5.84	3.50	0.79	0.50	0.61	625 x 1250	Aluminium
10-51A	10.24	5.64	1.55	0.90	1.34	1250 x 1250	Aluminium
30-96A	30.48	11.72	2.36	1.20	1.28	2500 x 1250	Aluminium
30-98A	30.48	12.50	1.60	1.20	0.81	1250 x 2500	Aluminium
50-89A	50.80	22.58	3.12	3.00	2.25	2500 x 1250	Aluminium
19-98S	19.05	7.26	1.71	0.90	3.47	1250 x 2500	Stainless 304