



## Genwork Expanded Metal Mesh Walkway Mesh

Expanded metal mesh has a diverse range of properties, which makes it extremely versatile for many uses and applications.

The mesh is formed from a single piece of metal, which means that there is nothing to work loose, no fretting strands or strained joints or welds.

### Cutting Service

In addition to stock panels we also offer a complete and comprehensive cut to size service, if you wish to have your panels cut to size or framed please follow the links below or down load planners.

'U' Edging Section  
Fabrication

Coatings – Self Colour, Galvanised, Bright Zinc plate and Powder Coated.

If you need anyhelp or advice please contact us.

### Walkway Mesh

Expanded Walkway mesh is perfectly suited to many industrial applications and is available in two dsitinct styles. Standard Walkway mesh is produced with smaller mesh openings which prevent onjects passing through the mesh, particullary useful if used as a catwalk over moving parts.

The other type of Walkway mesh is Long Bond series of meshes, which are designed to offer a large open area to maximise vision through the mesh and the long bond which joins each mesh provides excellant strength and grip.

Each Walkway mesh is able to offer excellent grip and structural strength due to the raised strands configuration.

There are a number of different Walkway meshes that are available.

### Volume Discounts

Quantities over +10 Panels = price on request

If there are any other forms of Raised mesh that you are looking for and not listed below, please don't hesitate to contact us

### Our range

Ref	Long Way	Short Way	Strand Width	Thickness	KG	Sheet Size LW x SW	Raw Material
8-78WRN	38.10	13.85	4.75	2.50	13.40	1220 x 1525	Mild Steel
38-76W	38.10	16.93	4.75	3.00	13.20	2440 x 1220	Mild Steel
60-96W	60.96	25.40	6.10	4.50	17.29	2440 x 1220	Mild Steel
60-96WR	60.96	25.40	6.10	4.50	17.29	1220 x 2440	Mild Steel
2-96W	121.92	33.87	6.35	4.50	13.20	2440 x 1220	Mild Steel
12-96WR	121.92	33.87	6.35	4.50	13.20	1220 x 2440	Mild Steel
12-99WR	121.92	35.85	9.53	6.00	24.98	1220 x 2440	Mild Steel
12-94W	121.92	38.10	13.25	6.00	32.60	2440 x 1220	Mild Steel
60-96WA	60.96	25.40	5.82	5.00	6.05	2500 x 1250	Aluminium

